

# Appendix J: Derivation of the Time Domain Solution of State Equations

## J.1 Derivation

Rather than using the Laplace transformation, we can solve the equations directly in the time domain using a method closely allied to the classical solution of differential equations. We will find that the final solution consists of two parts that are different from the forced and natural responses

First, assume a homogeneous state equation of the form

$$\dot{\mathbf{x}}(t) = \mathbf{A}\mathbf{x}(t) \tag{J.1}$$

Since we want to solve for  $\mathbf{x}$ , we assume a series solution, just as we did in elementary scalar differential equations. Thus,

$$\mathbf{x}(t) = \mathbf{b}_0 + \mathbf{b}_1 t + \mathbf{b}_2 t^2 + \dots + \mathbf{b}_k t^k + \mathbf{b}_{k+1} t^{k+1} + \dots \tag{J.2}$$

Substituting Eq. (J.2) into (J.1) we get

$$\begin{aligned} \mathbf{b}_1 + 2\mathbf{b}_2 t + \dots + k\mathbf{b}_k t^{k-1} + (k+1)\mathbf{b}_{k+1} t^k + \dots \\ = \mathbf{A}(\mathbf{b}_0 + \mathbf{b}_1 t + \mathbf{b}_2 t^2 + \dots + \mathbf{b}_k t^k + \mathbf{b}_{k+1} t^{k+1} + \dots) \end{aligned} \tag{J.3}$$

Equating like coefficients yields

$$\mathbf{b}_1 = \mathbf{A}\mathbf{b}_0 \tag{J.4a}$$

$$\mathbf{b}_2 = \frac{1}{2}\mathbf{A}\mathbf{b}_1 = \frac{1}{2}\mathbf{A}^2\mathbf{b}_0 \tag{J.4b}$$

⋮

$$\mathbf{b}_k = \frac{1}{k!}\mathbf{A}^k\mathbf{b}_0 \tag{J.4c}$$

$$\mathbf{b}_{k+1} = \frac{1}{(k+1)!}\mathbf{A}^{k+1}\mathbf{b}_0 \tag{J.4d}$$

⋮

Substituting these values into Eq. (J.2) yields

$$\begin{aligned} \mathbf{x}(t) &= \mathbf{b}_0 + \mathbf{A}\mathbf{b}_0 t + \frac{1}{2}\mathbf{A}^2\mathbf{b}_0 t^2 + \dots + \frac{1}{k!}\mathbf{A}^k\mathbf{b}_0 t^k + \frac{1}{(k+1)!}\mathbf{A}^{k+1}\mathbf{b}_0 t^{k+1} + \dots \\ &= \left( \mathbf{I} + \mathbf{A}t + \frac{1}{2}\mathbf{A}^2 t^2 + \dots + \frac{1}{k!}\mathbf{A}^k t^k + \frac{1}{(k+1)!}\mathbf{A}^{k+1} t^{k+1} + \dots \right) \mathbf{b}_0 \end{aligned} \tag{J.5}$$

But, from Eq. (J.2),

$$\mathbf{x}(0) = \mathbf{b}_0 \tag{J.6}^1$$

Therefore,

$$\mathbf{x}(t) = \left( \mathbf{I} + \mathbf{A}t + \frac{1}{2}\mathbf{A}^2t^2 + \dots + \frac{1}{k!}\mathbf{A}^k t^k + \frac{1}{(k+1)!}\mathbf{A}^{k+1}t^{k+1} + \dots \right) \mathbf{x}(0) \tag{J.7}$$

Let

$$e^{\mathbf{A}t} = \left( \mathbf{I} + \mathbf{A}t + \frac{1}{2}\mathbf{A}^2t^2 + \dots + \frac{1}{k!}\mathbf{A}^k t^k + \frac{1}{(k+1)!}\mathbf{A}^{k+1}t^{k+1} + \dots \right) \tag{J.8}$$

where  $e^{\mathbf{A}t}$  is simply a notation for the matrix formed by the right-hand side of Eq. (J.8). We use this definition because the right-hand side of Eq. (J.8) resembles a power series expansion of  $e^{at}$ , or

$$e^{at} = \left( 1 + at + \frac{1}{2}a^2t^2 + \dots + \frac{1}{k!}a^k t^k + \frac{1}{(k+1)!}a^{k+1}t^{k+1} + \dots \right) \tag{J.9}$$

Using Eq. (J.7), we have

$$\mathbf{x}(t) = e^{\mathbf{A}t} \mathbf{x}(0) \tag{J.10}$$

We give a special name to  $e^{\mathbf{A}t}$ : it is called the *state-transition matrix*<sup>2</sup>, since it performs a transformation on  $\mathbf{x}(0)$ , taking  $\mathbf{x}$  from the initial state,  $\mathbf{x}(0)$ , to the state  $\mathbf{x}(t)$  at any time,  $t$ . The symbol,  $\Phi(t)$ , is used to denote  $e^{\mathbf{A}t}$ . Thus,

$$\Phi(t) = e^{\mathbf{A}t} \tag{J.11}$$

and

$$\mathbf{x}(t) = \Phi(t)\mathbf{x}(0) \tag{J.12}$$

There are some properties of  $\Phi(t)$  that we will use later when we solve for  $\mathbf{x}(t)$  in the text. From Eq. (J.12),

$$\mathbf{x}(0) = \Phi(0)\mathbf{x}(0) \tag{J.13}$$

Hence, the first property of  $\Phi(t)$  is

$$\Phi(0) = \mathbf{I} \tag{J.14}$$

where  $\mathbf{I}$  is the identity matrix. Also, differentiating Eq. (J.12) and setting this equal to Eq. (J.1) yields

$$\dot{\mathbf{x}}(t) = \dot{\Phi}(t)\mathbf{x}(0) = \mathbf{A}\mathbf{x}(t) \tag{J.15}$$

which, at  $t = 0$ , yields

$$\dot{\Phi}(0)\mathbf{x}(0) = \mathbf{A}\mathbf{x}(0) \tag{J.16}$$

<sup>1</sup> In this development we consider the initial time,  $t_0$ , to be 0. More generally,  $t_0 \neq 0$ . After completing this development, the interested reader should consult Appendix K on [www.wiley.com/college/nise](http://www.wiley.com/college/nise) for the more general solution in terms of initial time  $t_0 \neq 0$ .

<sup>2</sup> The state-transition matrix here is for the initial time  $t_0 = 0$ . The derivation in Appendix K on [www.wiley.com/college/nise](http://www.wiley.com/college/nise) for  $t_0 \neq 0$  yields  $\mathbf{x}(t) = e^{\mathbf{A}(t-t_0)}\mathbf{x}(t_0)$ .

Thus, the second property of  $\Phi(t)$  follows from Eq. (J.16):

$$\dot{\Phi}(0) = \mathbf{A} \quad (\text{J.17})$$

In summary, the solution to the homogeneous, or unforced, system is

$$\mathbf{x}(t) = \Phi(t)\mathbf{x}(0) \quad (\text{J.18})$$

where

$$\Phi(0) = \mathbf{I} \quad (\text{J.19})$$

and

$$\dot{\Phi}(0) = \mathbf{A} \quad (\text{J.20})$$

Let us now solve the forced, or nonhomogeneous, problem. Given the forced state equation

$$\dot{\mathbf{x}}(t) - \mathbf{A}\mathbf{x}(t) = \mathbf{B}\mathbf{u}(t) \quad (\text{J.21})$$

rearrange and multiply both sides by  $e^{-\mathbf{A}t}$ :

$$e^{-\mathbf{A}t}[\dot{\mathbf{x}}(t) - \mathbf{A}\mathbf{x}(t)] = e^{-\mathbf{A}t}\mathbf{B}\mathbf{u}(t) \quad (\text{J.22})$$

Realizing that the left-hand side is equal to the derivative of the product  $e^{-\mathbf{A}t}\mathbf{x}(t)$ , we obtain

$$\frac{d}{dt} [e^{-\mathbf{A}t}\mathbf{x}(t)] = e^{-\mathbf{A}t}\mathbf{B}\mathbf{u}(t) \quad (\text{J.23})$$

Integrating both sides yields

$$[e^{-\mathbf{A}t}\mathbf{x}(t)] /_0^t = e^{-\mathbf{A}t}\mathbf{x}(t) - \mathbf{x}(0) = \int_0^t e^{-\mathbf{A}\tau}\mathbf{B}\mathbf{u}(\tau)d\tau \quad (\text{J.24})$$

since  $e^{-\mathbf{A}t}$  evaluated at  $t = 0$  is the identity matrix (from Eq. (J.8)). Solving for  $\mathbf{x}(t)$  in Eq. (J.24) we obtain

$$\begin{aligned} \mathbf{x}(t) &= e^{-\mathbf{A}t}\mathbf{x}(0) + \int_0^t e^{-\mathbf{A}(t-\tau)}\mathbf{B}\mathbf{u}(\tau)d\tau \\ &= \Phi(t)\mathbf{x}(0) + \int_0^t \Phi(t-\tau)\mathbf{B}\mathbf{u}(\tau)d\tau \end{aligned} \quad (\text{J.25})$$

where  $\Phi(t) = e^{\mathbf{A}t}$  by definition.

## Bibliography

Timothy, L. K., and Bona, B. E. *State Space Analysis: An Introduction*. McGraw-Hill, New York, 1968.

Copyright © 2015 John Wiley & Sons, Inc. All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, scanning or otherwise, except as permitted under Sections 107 or 108 of the 1976 United States Copyright Act, without either the prior written permission of the Publisher, or authorization through payment of the appropriate per-copy fee to the Copyright Clearance Center, Inc. 222 Rosewood Drive, Danvers, MA 01923, website [www.copyright.com](http://www.copyright.com). Requests to the Publisher for permission should be addressed to the Permissions Department, John Wiley & Sons, Inc., 111 River Street, Hoboken, NJ 07030-5774, (201)748-6011, fax (201)748-6008, website <http://www.wiley.com/go/permissions>.

Founded in 1807, John Wiley & Sons, Inc. has been a valued source of knowledge and understanding for more than 200 years, helping people around the world meet their needs and fulfill their aspirations. Our company is built on a foundation of principles that include responsibility to the communities we serve and where we live and work. In 2008, we launched a Corporate Citizenship Initiative, a global effort to address the environmental, social, economic, and ethical challenges we face in our business. Among the issues we are addressing are carbon impact, paper specifications and procurement, ethical conduct within our business and among our vendors, and community and charitable support. For more information, please visit our website: [www.wiley.com/go/citizenship](http://www.wiley.com/go/citizenship).

The software programs and experiments available with this book have been included for their instructional value. They have been tested with care but are not guaranteed for any particular purpose. The publisher and author do not offer any warranties or restrictions, nor do they accept any liabilities with respect to the programs and experiments.

**AMTRAK** is a registered trademark of National Railroad Passenger Corporation. **Adobe** and **Acrobat** are trademarks of Adobe Systems, Inc. which may be registered in some jurisdictions. **FANUC** is a registered trademark of FANUC, Ltd. **Microsoft**, **Visual Basic**, and **PowerPoint** are registered trademarks of Microsoft Corporation. **QuickBasic** is a trademark of Microsoft Corporation. **MATLAB** and **SIMULINK** are registered trademarks of The MathWorks, Inc. **The Control System Toolbox**, **LTI Viewer**, **Root Locus Design GUI**, **Symbolic Math Toolbox**, **Simulink Control Design**, and **MathWorks** are trademarks of The MathWorks, Inc. **LabVIEW** is a registered trademark of National Instruments Corporation. **Segway** is a registered trademark of Segway, Inc. in the United States and/or other countries. **Chevrolet Volt** is a trademark of General Motors LLC. Virtual plant simulations pictured and referred to herein are trademarks or registered trademarks of Quanser Inc. and/or its affiliates. © 2010 Quanser Inc. All rights reserved. Quanser virtual plant simulations pictured and referred to herein may be subject to change without notice. **ASIMO** is a registered trademark of Honda.

Evaluation copies are provided to qualified academics and professionals for review purposes only, for use in their courses during the next academic year. These copies are licensed and may not be sold or transferred to a third party. Upon completion of the review period, please return the evaluation copy to Wiley. Return instructions and a free of charge return shipping label are available at [www.wiley.com/go/returnlabel](http://www.wiley.com/go/returnlabel). Outside of the United States, please contact your local representative.

#### *Library of Congress Cataloging-in-Publication Data*

Nise, Norman S.

Control systems engineering / Norman S. Nise, California State Polytechnic University, Pomona. — Seventh edition.  
1 online resource.

Includes bibliographical references and index.

Description based on print version record and CIP data provided by publisher; resource not viewed.

ISBN 978-1-118-80082-9 (pdf) — ISBN 978-1-118-17051-9 (cloth : alk. paper)

1. Automatic control—Textbooks. 2. Systems engineering—Textbooks. I. Title.

TJ213

629.8—dc23

2014037468

Printed in the United States of America

10 9 8 7 6 5 4 3 2 1